



# Hope Industrial Systems, Inc.

HopeIndustrial.co.uk • HopeIndustrial.eu • Phone: UK: +44 (0) 20 7193 2618 / EU: +31 20 241 0853  
E-mail: UK: sales@HopeIndustrial.co.uk / EU: sales@HopeIndustrial.eu

## Data Sheet: Universal Mount Monitors and Touch Screens

IP65/IP66, NEMA 12/4/4X  
15"/17"/19"/19.5"/22"/23.8"

### Features

- ▶ 15", 17", 19", 19.5", 22", or 23.8" active-matrix LCD
- ▶ Sealed to IP65/IP66 Standards
- ▶ Bright, high contrast, and ultra-wide viewing angles
- ▶ Touch Screen, Glass, Acrylic, and Food Protection window options
- ▶ VESA and side mounting holes standard on all models
- ▶ Cable lengths from 1.5 m to 300 m
- ▶ Small size – only 71 mm to 83 mm deep
- ▶ Black carbon steel and stainless steel enclosures
- ▶ Long-life backlights – up to 60,000 hours to half brightness
- ▶ Industrial Certifications: CE, UKCA, IEC 60721-3, UL 50E, UL/EN/IEC62368-1, UL Listed

### Product Description

Hope Industrial Systems' Universal Mount Industrial Monitors are designed to provide the industrial user with excellent picture quality and rugged design for reliable continuous operation.

Universal Mount Monitors are extremely versatile and can be mounted to the floor on a pedestal, attached to a wall, column, or post, or even hung from the ceiling: anywhere in the factory a display or touch screen is needed.

These monitors are backed by industrial certifications (including 3rd-party environmental testing) and an industry-leading 5-year warranty.

### Optional Accessories

- ▶ Yoke Mounts
- ▶ Multiple cable exit options
- ▶ KVM Extenders
- ▶ Benchtop mounting kits
- ▶ Free-standing pedestals
- ▶ Arm and wall mount kits
- ▶ Keyboards and keyboard trays
- ▶ Cable options up to 300 m

RoHS

CE

cUL<sub>US</sub>



Universal Mount Monitor on Industrial Yoke Mount with KVM Extender.



Universal Mount Monitor mounted on IP65/IP66 rated Heavy Industrial Arm Mount.



Full workstation configuration with PC enclosure, keyboard, yoke, and pedestal.



Universal Mount Monitor mounted on VESA Radial Arm.



### About Hope Industrial Systems

Hope Industrial provides industrial flat panel monitors and touch screens with superior quality and up-to-date features that are relevant to industrial applications.

We house this advanced technology in a variety of rugged enclosures that allow the user to put their displays wherever they are needed in the factory. We assure our customers of high reliability over time and back it up with an industry-leading warranty.

We provide all of these benefits at a price that is significantly less than comparable industrial offerings. And finally, we offer the best sales, support and service in the industry:

- ▶ 5-year limited warranty on all monitors, return shipping included
- ▶ 24-48-hour repair turnaround (most models)
- ▶ Same day dispatch lead time (most models)
- ▶ 30-day money-back guarantee

# Universal Mount Industrial Monitors and Touch Screens

## Monitor Overview

### Rear View

Depth only:  
 71.1 mm (15")  
 82.6 mm (17",  
 19", 19.5", 22",  
 23.8")

Optional Yoke  
 mount provides  
 full tilt/swivel



IP65/IP66 rated enclosures available in  
 Black Carbon Steel or Stainless Steel

VESA mounting  
 holes standard on  
 all models!

15", 17", 19", 19.5", 22",  
 or 23.8" Monitor with:  
 - Touch Screen,  
 - Tempered Glass, or  
 - Acrylic Window

Sealed rear cover  
 provides IP65/IP66  
 rated protection

### Rear View with KVM Extender Option

Depth with KVM  
 Extender only:  
 116.8 mm (15")  
 124.5 mm (17", 19",  
 19.5", 22", 23.8")

External rear access  
 to monitor controls

Optional modular  
 KVM Extender allows  
 placement of the display  
 up to 300 m away from  
 computer!



## Cable Exit Options



Opening to Internal  
 Connectors



Compression Gland  
 (IP22 or IP65/IP66)



Conduit Cable Exit  
 (IP65/IP66)



Pilot Hole Cover Plate  
 (IP65/IP66)

## Mounting Options

### Heavy Industrial Mounts

Rugged designs ideal for even the harshest environments. Available in IP65/IP66 Rated stainless or black powder-coated steel.

#### Heavy Industrial Arm Mounts

Space-saving designs with full  
 range of motion

Adjustment  
 knobs lock  
 monitor tilt



Double Extension Arm



Single Extension Arm

Rated at up  
 to 45 kg!



Wall Yoke

#### Heavy Industrial Yokes and Pedestals

Extremely sturdy free-standing configurations

Short-Travel  
 Keyboard

Small PC  
 Enclosure with  
 integrated  
 cooling and  
 power supply

3/16" gauge steel  
 floor mounting  
 bracket prevents  
 vibration



Yoke provides full  
 range tilt and swivel

Cables route  
 through Pedestal

PC  
 Enclosure

1m tall Pedestal,  
 3.2mm thick,  
 102mm  
 square tube



Optional  
 Floor Stand

### VESA Mounts

VESA holes allow for mounting on  
 a Wall, Bench, Post, or Column



VESA Radial Arm



VESA Wall  
 Mount



VESA  
 Benchtop  
 Stand

# Universal Mount Industrial Monitors and Touch Screens

Model No. (Revision):	UM15 (Rev. H)	UM17 (Rev. H)	UM19 (Rev. H)	UM19.5 (Rev. B)	UM22 (Rev. C)	UM23.8 (Rev. A)
<b>Display</b>						
Type	Thin-film transistor (TFT) Active Matrix Liquid Crystal, LED Backlit					
Size	381 mm (15") diagonal	432 mm (17") diagonal	483 mm (19") diagonal	495 mm (19.5") diagonal	559 mm (22") diagonal	605 mm (23.8") diagonal
Image Size (W x H)	304 mm x 228 mm	338 mm x 270 mm	375 mm x 300 mm	435 mm x 239 mm	474 mm x 296 mm	527 mm x 296 mm
Native Resolution*	XGA (1024 x 768 @ 60Hz)	SXGA (1280 x 1024 @ 60 Hz)		HD 1080p (1920 x 1080 @ 60Hz)	WSXGA+ (1680 x 1050 @ 60Hz)	HD 1080p (1920 x 1080 @ 60Hz)
Aspect Ratio	4:3	5:4		16:9	16:10	16:9
Pixel Pitch	0.297mm x 0.297mm	0.264mm x 0.264mm	0.293mm x 0.293mm	0.2265mm x 0.221mm	0.282mm x 0.282mm	0.2745mm x 0.2745mm
Number of Colours	16.7 million					
Brightness (white)	400 nits (cd/m <sup>2</sup> )	250 nits (cd/m <sup>2</sup> )				350 nits (cd/m <sup>2</sup> )
Viewing Angle (Hori/Vert)	170° / 170°	170° / 160°	178° / 178°		170° / 160°	178° / 178°
Contrast Ratio	1500:1	1000:1	1000:1 (typical); 20M:1 (dynamic)	3000:1	1000:1 (typical); 10M:1 (dynamic)	1000:1
Backlight Brightness half-life	60,000 hours		40,000 hours	50,000 hours		40,000 hours
<b>Video</b>						
Input Connectors	HD-15, DVI-I		HD-15, DVI-D	DVI-I, DisplayPort	HD-15, DVI-I	DVI-I, DisplayPort
Inputs using Adapter	HDMI, HDMI Mini, HDMI Micro, DisplayPort, DisplayPort Mini, BNC			HDMI, HDMI Mini, HDMI Micro, DisplayPort Mini, VGA, BNC	HDMI, HDMI Mini, HDMI Micro, DisplayPort, DisplayPort Mini, BNC	HDMI, HDMI Mini, HDMI Micro, DisplayPort Mini, VGA, BNC
Input Signal Formats**	RGB Analogue, Sync Types: Separate (Sep), Composite (Comp), Sync on Green (SoG); DVI		RGB Analogue, Sync Type: Separate; DVI	RGB, Sync Types: Sep, Comp, SoG; DVI; DisplayPort	RGB, Sync Types: Separate, Composite, Sync on Green; DVI	RGB, Sync Types: Sep, Comp, SoG; DVI; DisplayPort
Horizontal Scan	31-73 kHz			24-82 kHz		
Vertical Scan	50-75 Hz					
Response Rate	35 ms	5 ms	14 ms	25 ms	5 ms	14 ms
<b>Electrical</b>						
Monitor Input	100 to 240 VAC, 1.5/0.75 A, 60/50 Hz or 9.6 to 36.6 VDC, 2.5 to 0.65 A			100 to 240 VAC, 0.6/0.3 A, 60/50 Hz and 10.8 to 26.4 VDC, 2.3 to 0.9 A	100 to 240 VAC, 1.5/0.75 A, 60/50 Hz or 9.6 to 36.6 VDC, 2.5 to 0.65 A	100 to 240 VAC, 0.6/0.3 A, 60/50 Hz and 10.8 to 26.4 VDC, 2.3 to 0.9 A
Power Consumption	~16.8 W	~20 W	~16 W	~27 W	~26 W	~27 W
Power Management	< 4 W		< 0.5 W	< 2 W	< 0.5 W	< 2 W
<b>Environmental</b>						
Temperature	Operating: 0° to 50°C; Storage: -20° to 60°C					
Humidity	20% to 90% non-condensing					
Operating Shock	15 g, 6 msec, half-sine					
Vibration	Operating (sine): 1.0 g, swept sine 9-500 Hz; Transport (random): 0.1g <sup>2</sup> /Hz, 10-200 Hz; 0.03g <sup>2</sup> /Hz, 200-2000 Hz					
Altitude	Operating: up to 3.05 m; Non-operating: up to 12.19 m					
<b>Functional</b>						
Control Panel Buttons	Power On/Off button, Control Function buttons					
On-Screen Display Menus	Picture, Color, Image, OSD, Setup, Information (other options depending on model)					
<b>Physical</b>						
Enclosure Type	Self-contained enclosure					
Enclosure Rating	Black powder-coated carbon steel (black powder-coated aluminium rear cover): IP22 or IP65/IP66; NEMA Type 2 or 4 Stainless steel: IP22 or IP65/IP66 (depending on cable exit); NEMA Type 2 or 4X					
Enclosure Bezel (W x H)	416.6 mm x 330.2 mm	416.6 mm x 354.1 mm	467.4 mm x 397.5 mm	537.7 mm x 340.1 mm	546.1 mm x 376.9 mm	603.3 mm x 383.0 mm
Depth	71.1 mm (116.8 mm with KVM Extender)	82.6 mm (124.5 mm with KVM Extender)				
Net Weight	Carbon steel: 5.90kg Stainless steel: 7.26kg	Carbon steel: 6.80kg Stainless steel: 8.16kg	Carbon steel: 8.16kg Stainless steel: 9.53kg	Carbon steel: 8.89kg Stainless steel: 10.0kg	Carbon steel: 9.07kg Stainless steel: 11.34kg	Carbon steel: 11.7kg Stainless steel: 13.5kg
Shipping Weight	Carbon steel: 7.26kg Stainless steel: 8.6kg	Carbon steel: 8.16kg Stainless steel: 9.5kg	Carbon steel: 9.53kg Stainless steel: 10.9kg	Carbon steel: 11.34kg Stainless steel: 12.3kg	Carbon steel: 10.43 kg Stainless steel: 12.7 kg	Carbon steel: 14.5kg Stainless steel: 14.5kg
Window Options	All Models: <ul style="list-style-type: none"> <li>Single-Touch Resistive Touch Screen</li> <li>Tempered Glass window (non-touch)</li> <li>Acrylic window (non-touch) (n/a 19.5, 23.8)</li> </ul>			HIS-UM19.5 and HIS-UM23.8 Models only: <ul style="list-style-type: none"> <li>Multi-Touch PCAP Touch Screen</li> <li>Food Protection window (non-touch)</li> </ul>		
<b>Compliances and Certifications</b>						
Electrical	CE, UKCA, UL/EN/IEC62368-1, UL/EN/IEC60950-1, UL Listed for US and Canada, FCC Class A, CAN ICES-3A/NMB-3A, NOM					
Environmental	IEC 60721-3 (Reliability), WEEE					
Enclosure	UL 50E					

\* A full list of supported video standards may be found on our website.  
 \*\* NTSC/PAL composite input available. Call for details (+44 (0) 20 7193 2618).